



# Venus collection



**BoFloor**  
Quality that endures

12 designs available in dry back and rigid click

- 8 wood designs
- 4 stone designs
- 5 herringbone designs



# PLANKS

8 designs available in dry back & rigid click

✓ Suitable underfloor heating

✓ Suitable for wet rooms

✓ PUR *Ecoprotec*<sup>TM</sup>  
anti-scratch & antibacterial  
surface treatment



**Fresh Oak Light Greige**

OFT-055-001 (dry back)  
OFM-055-001N (rigid click)



**Bavarian Oak Honey**

OFT-055-002 (dry back)  
OFM-055-002N (rigid click)



**Delicate Oak Amber**

OFT-055-003 (dry back)  
OFM-055-003N (rigid click)



**Delicate Oak Natural**

OFT-055-004 (dry back)  
OFM-055-004N (rigid click)



**Aspen Oak Dark Greige**

OFT-055-005 (dry back)  
OFM-055-005N (rigid click)



**Nordic Oak Light Natural**

OFT-055-009 (dry back)  
OFM-055-009N (rigid click)



**Nordic Oak Greige**

OFT-055-010 (dry back)  
OFM-055-010N (rigid click)



**Fresh Oak Natural**

OFT-055-011 (dry back)  
OFM-055-011N (rigid click)





Fresh Oak Natural



# PLANKS

## Dry back

Wear layer: 0,55 mm  
Total thickness: 2,5 mm  
Size: 228,6 x 1422,4 mm

Weight /  $m^2$  : 4,50 kg  
Nb planks / box: 14  
Nb boxes / pallet: 48  
 $m^2$  / box: 4,55  
 $m^2$  / pallet: 218,40

## Rigid click

Wear layer: 0,55 mm  
Total thickness: 5 mm  
Size: 180 x 1220 mm

## UNIPUSH click system

Weight /  $m^2$  : 8,20 kg  
Nb planks / box: 10  
Nb boxes / pallet: 55  
 $m^2$  / box: 2,20  
 $m^2$  / pallet: 121



Impact sound reduction 21dB

# HERRINGBONES

5 designs available in dry back

Wear layer: 0,55 mm

Total thickness: 2,5 mm

Size: 150 x 750 mm

Weight /  $m^2$  : 4,50 kg

Nb planks / box: 32

Nb boxes / pallet: 60

$m^2$  / box: 3,6

$m^2$  / pallet: 216



**Fresh Oak Light Greige**

OFT-055-301



**Delicate Oak Amber**

OFT-055-303



**Nordic Oak Light Natural**

OFT-055-309



**Nordic Oak Greige**

OFT-055-310



**Fresh Oak Natural**

OFT-055-311

# TILES

4 designs available in dry back & rigid click

✓ Suitable underfloor heating

✓ Suitable for wet rooms

✓ PUR *Ecoprotec*<sup>TM</sup>  
anti-scratch & antibacterial  
surface treatment



**Scratched Concrete Pearl**

OFT-055-012 (dry back)  
OFM-055-012N (rigid click)



**Scratched Concrete Ash**

OFT-055-013 (dry back)  
OFM-055-013N (rigid click)



**Concrete Terreno Natural**

OFT-055-014 (dry back)  
OFM-055-014N (rigid click)



**Concrete Terreno Dark Grey**

OFT-055-015 (dry back)  
OFM-055-015N (rigid click)





Scratched concrete pearl

# TILES

## Dry back

Wear layer: 0,55 mm

Total thickness: 2,5 mm

Size: 457,2 x 914,4 mm

Weight /  $m^2$  : 4,28 kg

Nb planks / box: 10

Nb boxes / pallet: 42

$m^2$  / box: 4,18

$m^2$  / pallet: 175,56

## Rigid click

Wear layer: 0,55 mm

Total thickness: 5 mm

Size: 305 x 610 mm

## I4F click system

Weight /  $m^2$  : 8,06 kg

Nb planks / box: 9

Nb boxes / pallet: 54

$m^2$  / box: 1,67

$m^2$  / pallet: 90,18



Impact sound reduction 21dB





**a** Havikweg 17  
6374 AZ Landgraaf (NL)

Industrial area Abdissenbosch  
Parkstad 3381

**t** (+31)045-5322277

**e** info@bofloor.biz

**www.bofloor.nl**